



SPECIFICATIONS	
Power Supply	AC24V
Operating temperature rang	-30°C~+50°C
Maerial	SUS316
Roating speed	12"/Sec
Roating angle	0~350° & ±90°
Weight	25Kg
IP GRADE	IP 66

This drawing is the property of CMR KOREA Co.,Ltd. and must not be wholly or partly copied, reproduced, utilized or published without written consent. This is a CADAM drawing and should not be corrected by hand.

SHT. NO.

GENERAL TOLERANCE FOR BOX OUTLINE		GENERAL TOLERANCE FOR SENSOR & FITTING HOLE	
NOMINAL MEASURE	TOLERANCES	NOMINAL MEASURE	TOLERANCES
OVER	MAX	OVER	MAX
1	± 1.0	1	± 0.3
100	± 2.0	4	± 0.5
200	± 3.0	16	± 1.0
500	± 5.0	63	± 2.0
1000	± 7.0	250	± 2.5

REV.	LOC	DATE
△		
△		

APP.	LOC	DATE	TITLE
20020101			WATER PROOF HOUSING WITH PAN/TILT DRIVER (MODEL : WTPH-200)
CHK.			
DWG.	20020101		

PROJE-CTION	UNIT	SCALE
N / A	mm	N / S

SIZE	A4
CMR	CMR KOREA CO., LTD.
DRAWING NO.	CTVHO-01-001

